



ADM

SERIES



THE DELTAWEIGHER



EC



ADM

FEATURES

- OIML-R76 and EC Class III Type Approved
- Washdown Construction: - Designed According to IP66
- Support 1/6000 ~ 1/7500 Display Resolution for Non-OIML Applications*
- Support Metric and Avoirdupois Weight Units and Conversion
- User Friendly Operation
- Equipped with Power On Zero Tracking, Manual Zero, Auto Calibration, Smart Power Saving and Automatic Tare Functions
- Wide Angle LCD Display Digits
- Protection Devices against Overload and Shock
- Dual Power Source: By Built-in Rechargeable Battery or Power Adaptor
- Long Battery Operating Time: 120 Hours Plus
- Completed with Low Battery and Charging Status Indicators
- Stainless Steel Platter Cover, Adjustable Feet, Built-in Rechargeable Battery, Power Adaptor and Bubble Level Included

- Display Resolution of Avoirdupois Weight Units always = 1/3000

OPTIONS AVAILABLE

- Rear Display
- Backlight
- RS232C Interface

SPECIFICATIONS

Model No.	Capacity	Division	
		OIML	Non-OIML
ADM-1500	1500g	0.5g	NIL
ADM-3000	3000g	1g	0.5g
ADM-6000	6000g	2g	1g
ADM-15K	15kg	0.005kg	0.002kg
ADM-30K	30kg	0.01kg	0.005kg
Tare Range	Full Tare Range (Subtractive)		
Platter	215 x 250mm Stainless Steel		
Power Source	Built-in Rechargeable Battery or External AC/DC Power Adaptor		
Operation Environment	0°~40°C (32°~104°F), Non-condensed. R.H. ≤ 85%		

* Specifications subject to change without notice



unit = mm



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taippei Hsien Taiwan R.O.C.
Tel : +886-2-29180121 (12 Lines) Fax : +886-2-29181508 · 29183652 · 29112178-7
<http://www.uwe-scale.com.tw> e-mail: uwe@ms6.hinet.net

Mar 2003 Designed by DAILY
Printed in Taiwan